



Standard Hollow Tine - .750MT x 4.750L x .475OD R59-3690



Details

Designed to remove a soil core, R&R Standard Hollow Tines are constructed from case hardened tubular steel and are the most economical tines available. Case hardening hardens the inner and outer surfaces of the tine wall to over RC55 for added wear.

Replaces

| | |
|--------------|---|
| John Deere | TCU17449 |
| R&R Products | R100-3633, R523421, RMT2964, RTCU17449 |
| Toro | 59-3690 |

Specifications

| | |
|-------------------------------------|------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Standard Hollow |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 4.75 in (121mm) |
| D - Tine Tip Outside (Hole) Dia. | .475 in (12.1mm) |
| E - Tine Tip Inside (Core) Dia. | .330 in (8.4mm) |
| F - Tine Wall Thickness | .049 in (1.2mm) |
| Savings | Volume Buy |

Fits Models

John Deere Aercore 1000
John Deere Aercore 1500
John Deere Aercore 2000
John Deere Aercore 800
Ryan GA30
Toro Fairway Aerator

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225
+34 931 130 054

<https://evergreen.rrproducts.com/>



Standard Hollow Tine - .750MT x 4.750L
x .475OD
R59-3690



Toro Greens Aerator
Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225
+34 931 130 054

<https://evergreen.rrproducts.com/>