



Alloy Machined Side-Eject Tine with Carbide Tip - .375MT x 5.000L x .545OD

R108-9124



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine. A carbide tip is then added for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines.

Replaces

Toro 108-9124

Specifications

| | |
|----------------------------------|--|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Machined Side-Eject with Carbide Tip |
| B - Tine Mounting Dia. | .375 in (9.5mm) |
| C - Tine Length | 5 in (127mm) |
| Carbide Tip | Carbide Tip |
| D - Tine Tip Outside (Hole) Dia. | .545 in (13.8mm) |
| E - Tine Tip Inside (Core) Dia. | .400 in (10.2mm) |
| F - Tine Wall Thickness | .065 in (1.7mm) |
| Savings | Volume Buy |

Fits Models

Toro ProCore 1298

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225
+34 931 130 054

<https://evergreen.rrproducts.com/>



Alloy Machined Side-Eject Tine with Carbide Tip - .375MT x 5.000L x .545OD

R108-9124



Toro ProCore 440
Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225
+34 931 130 054

<https://evergreen.rrproducts.com/>