


Alloy Hollow Tine - .750MT x 6.500L x .470OD





Details

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

Replaces

Toro 108-9138

Specifications

Manufacturer R&R Products
A - Tine Type Alloy Hollow
B - Tine Mounting .750 in (19mm)
Dia.
C - Tine Length 6.5 in (165mm)
D - Tine Tip Outside .470 in (11.9mm)

(Hole) Dia. E - Tine Tip Inside

nside .300 in (7.6mm)

(Core) Dia.

F - Tine Wall .058 in (1.5mm)

Thickness

Savings Volume Buy

Fits Models

Toro ProCore 1298
Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225 +34 931 130 054

https://evergreen.rrproducts.com/



R108-9138

Alloy Hollow Tine - .750MT x 6.500L x .4700D



Toro ProCore 648s

EvergreenC/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225
+34 931 130 054

https://evergreen.rrproducts.com/