



# Alloy Hollow Side-Eject Tine - .750MT x 5.750L x .570OD R108-9164



## Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

## Replaces

Toro 108-9164

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow Side-Eject
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	5.75 in (146mm)
D - Tine Tip Outside (Hole) Dia.	.570 in (14.5mm)
E - Tine Tip Inside (Core) Dia.	.400 in (10.2mm)
F - Tine Wall Thickness	.058 in (1.5mm)

## Fits Models

Toro Fairway Aerator  
Toro ProCore 1298  
Toro ProCore 440  
Toro ProCore 648  
Toro ProCore 660  
Toro ProCore 864  
Toro ProCore 880  
Toro ProCore 648s

## Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225  
+34 931 130 054

<https://evergreen.rrproducts.com/>