



Alloy Machined Side-Eject Tine - .375MT x 5.500L x .625OD R108-9290



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

Toro 108-9290, R108-9290

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.375 in (9.5mm)
C - Tine Length	5.500 in (140mm)
D - Tine Tip Outside (Hole) Dia.	.625 in (15.9mm)
E - Tine Tip Inside (Core) Dia.	.500 in (12.7mm)
F - Tine Wall Thickness	.065 in (1.7mm)

Fits Models

Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225
+34 931 130 054

<https://evergreen.rrproducts.com/>



Alloy Machined Side-Eject Tine - .375MT
x 5.500L x .625OD
R108-9290



Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225
+34 931 130 054

<https://evergreen.rrproducts.com/>