

Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 4.750L x .4250D R201509





Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine. A carbide tip is then added for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines.

Replaces

R&R Products R108-9170 Toro 108-9170

Specifications

Manufacturer

A - Tine Type Alloy Hollow Side-Eject with Carbide Tip B - Tine Mounting .750 in (19mm) Dia. C - Tine Length 4.75 in (121mm) Carbide Tip Carbide Tip D - Tine Tip Outside .425 in (10.7mm) (Hole) Dia. E - Tine Tip Inside .275 in (7mm) (Core) Dia.

R&R Products

.072 in (1.8mm)

Fits Models

Jacobsen GA-24

F - Tine Wall

Thickness

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225 +34 931 130 054

https://evergreen.rrproducts.com/



Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 4.750L x .4250D R201509



Ryan Greensaire II

Toro Greens Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225 +34 931 130 054

https://evergreen.rrproducts.com/