

Alloy Machined Side-Eject Tine - .375MT x 3.500L x .565OD



R201631



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Specifications

Manufacturer R&R Products

A - Tine Type Alloy Machined Side-

Eject

B - Tine Mounting .375 in (9.5mm)

Dia.

C - Tine Length 3.5 in (89mm)
D - Tine Tip Outside .565 in (14.4mm)

(Hole) Dia.

E - Tine Tip Inside .435 in (11mm)

(Core) Dia.

F - Tine Wall .062 in (1.6mm)

Thickness

Fits Models

Greencare CoreMaster
John Deere Aercore 1000
John Deere Aercore 1500
John Deere Aercore 2000
John Deere Aercore 800
Toro Greens Aerator

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225

https://evergreen.rrproducts.com/