



# Alloy Machined Side-Eject Tine - .500MT x 3.500L x .445OD R201634



## Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.500 in (12.7mm)
C - Tine Length	3.5 in (89mm)
D - Tine Tip Outside (Hole) Dia.	.445 in (11.3mm)
E - Tine Tip Inside (Core) Dia.	.320 in (8.1mm)
F - Tine Wall Thickness	.049 in (1.2mm)

## Fits Models

Jacobsen Aero King 30  
Jacobsen GA-24  
Ryan GA30  
Ryan Greensaire II

## Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225  
+34 931 130 054

<https://evergreen.rrproducts.com/>