

Alloy Hollow Side-Eject Tine - .750MT x 4.750L x .6700D R201645





Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

Specifications

| Manufacturer | R&R Products |
|----------------------|-------------------------|
| A - Tine Type | Alloy Hollow Side-Eject |
| B - Tine Mounting | .750 in (19mm) |
| Dia. | |
| C - Tine Length | 4.75 in (121mm) |
| D - Tine Tip Outside | .670 in (17mm) |
| (Hole) Dia. | |
| E - Tine Tip Inside | .500 in (12.7mm) |
| (Core) Dia. | |
| F - Tine Wall | .072 in (1.8mm) |
| Thickness | |

Fits Models

Toro Greens Aerator Toro ProCore 1298 Toro ProCore 440 Toro ProCore 648 Toro ProCore 660 Toro ProCore 864 Toro ProCore 880 Toro ProCore 648s

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225 +34 931 130 054 https://evergreen.rrproducts.com/