



Alloy Hollow Tine - .750MT x 5.750L x .670OD R201652



Details

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

Specifications

| | |
|----------------------------------|------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Hollow |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 5.75 in (146mm) |
| D - Tine Tip Outside (Hole) Dia. | .670 in (17mm) |
| E - Tine Tip Inside (Core) Dia. | .500 in (12.7mm) |
| F - Tine Wall Thickness | .072 in (1.8mm) |

Fits Models

Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

Evergreen

C/. Bartomeu Amat, 2, Entlo 1 Terrassa, 08225
+34 931 130 054

<https://evergreen.rrproducts.com/>